

Royal Royco 363

INGREDIENTS	CAS NO	%	8HR OEL
naphthenic distillate, light, hydrotreated (severe)	64742-53-6.	75-85	5 mg/m3
naphthenic distillate, light, solvent-refined (severe)	64741-97-5.	5-15	5 mg/m3
distillates, petroleum, middle, hydrotreated	64742-46-7.	1-5	5 mg/m3
calcium dinonyl naphthalenesulfonate	57855-77-3	1-10	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
Does not mix with water.
Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together