

TDP Prochinor SLK 33

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	<2	350 mg/m3
solvent naphtha petroleum, heavy aromatic	64742-94-5	>30	-



UN No: **3082**
 Hazchem Code: **•3Z**
 DG Class: **9**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **III**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Flammable.
 Toxic smoke/fumes in a fire.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Does not mix with water.
 Floats on water. Flammable.
 Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Eliminate ignition sources.
 Pollutant.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together