

International GTA 220

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	>50	350 mg/m3
ethylbenzene	100-41-4	10-25	434 mg/m3
n-butanol	71-36-3	25-50	N/A



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

















Harmful by inhalation. Harmful in contact with skin. Harmful if swallowed. Irritating to respiratory system.

Effects: Irritating to skin.

Risk of serious damage to eyes.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE

















Appropriate engineering controls:

Acute Health

Local Exhaust Ventilation recommended.

Consider chemical goggles.

Glasses: Gloves:

1.TEFLON 2.PE/EVAL/PE 3.PVA

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Store in cool, dry, protected area. Restrictions on

Storage and Transportation:

Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES









Liquid. Does not mix with water. Floats on water. Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice. Do Swallowed: NOT give milk or oil. Do NOT give alcohol. Wash with running water (15 mins). Medical Eye: attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Fresh air. Rest, keep warm. If breath shallow, give

oxygen. Medical attention. Evaluate for respiratory distress. Consider lavage

Doctor: with cuffed tube. NO adrenalin.

Fire Fighting: Foam.

Inhaled:

Advice To

Spills and

Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all

objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive







Toxic

Radioactive Oxidizing x x x x

- Must not be stored together