

Schlumberger Flac D112 Fluid-Loss Additive

INGREDIENTS	CAS NO	%	8HR OEL
hydroxyethylcellulose	9004-62-0	>80	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **None**
 Subsidiary Risk: **None**
 Packing Group: **None**
 Poisons Schedule: **Not Applicable**

**NFPA Rating:**

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls: General Exhaust Ventilation adequate.

Glasses: Consider chemical goggles.

Respirator: Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Toxic smoke/fumes in a fire.

PROPERTIES



Solid. Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Wash with soap

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Treat symptomatically.

Fire Fighting: Water spray/ fog.

Spills and Disposal: Eliminate ignition sources. Avoid dust. Sweep shovel to safe place.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together