

## BOSTICK ADH 4045

INGREDIENTS	CAS NO	%	8HR OEL
methyl ethyl ketone	78-93-3	37.3	445 mg/m3
acetone	67-64-1	36.5	1185 mg/m3



UN No: 1133  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes and respiratory system.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PROPERTIES



Liquid.  
 Mixes with water. Highly flammable.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	No antidote. Supportive care.
<b>Fire Fighting:</b>	Keep containers cool. Water spray/ fog. Foam - alcohol type.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.BUTYL 3.TEFLON

## Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together