

## Ampol Delo 500 Multigrade SAE 15W-40

## INGREDIENTS

paraffinic distillate, heavy, solvent-dewaxed (severe)

## CAS No

64742-65-0.

## %

73-85

## 8hr OEL

-

## NFPA RATING



NFPA Rating: 0: Minimum, 1: Low, 2: Moderate, 3: High, 4: Extreme

UN No: Not Applicable

Hazchem Code: Not Applicable

DG Class: Not Applicable

Subsidiary Risk: Not Applicable

Packing Group: Not Applicable

Poisons Schedule: Not Available

## PROPERTIES

Liquid. Does not mix with water. Floats on water. Combustible.

## HEALTH HAZARD INFORMATION



## ACUTE HEALTH EFFECTS:

Vapours may cause drowsiness and dizziness.

## CHRONIC HEALTH EFFECTS:

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

X: Must not be stored together

## PRECAUTIONS FOR USE



## APPROPRIATE ENGINEERING CONTROLS:

General Exhaust Ventilation adequate.

## GLASSES:

Not normally required

## GLOVES:

When handling larger quantities:

PVC chemical resistant type.

## RESPIRATOR:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 &amp; 1715, EN 143:2000 &amp; 149:2001, ANSI Z88 or national equivalent)

## STORAGE AND TRANSPORTATION:

Store in cool, dry, protected area.

## FIRE/EXPLOSION HAZARD:

Toxic smoke/fumes in a fire.

## EMERGENCY



## FIRST AID

## SWALLOWED:

Give water (if conscious). Seek medical advice.

## EYE:

Wash with running water.

## SKIN:

Remove contaminated clothing. Wash with soap &amp; water.

## INHALED:

Fresh air. Rest, keep warm.

## ADVICE TO DOCTOR:

Emesis generally unnecessary. Debride for subcutaneous injection.

## FIRE FIGHTING:

Foam.

## SPILLS AND DISPOSAL:

Eliminate ignition sources.

Absorb with dry agent.

Stop leak if safe to do so.

For further information call Environmental Protection: 880-9714 (DH) or 427-0158 (JID)

For proper disposal methods and locations for the chemical or chemical contaminated material, contact the Environmental Engineering Division on 880-9767