

Kentile adhesive 1711

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	4-5	191 mg/m3
methanol	67-56-1	<2	262 mg/m3
naphtha petroleum, isoparaffin, hydrotreated	64742-48-9.	<3	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

Chronic Health Effects: Possible risk of harm to the unborn child.
 * – *limited evidence*

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES



Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — *Must not be stored together*