

Fisher Scientific Silver, Reference Standard Solution 1000 Ppm

| INGREDIENTS | CAS NO | % | 8HR OEL |
|--|-----------|------|------------------------|
| NITRIC ACID | 7697-37-2 | 2 | 5.2 mg/m ³ |
| Silver nitrate, potassium nitrate applicator | 7761-88-8 | 0.15 | 0.01 mg/m ³ |
| Water | 7732-18-5 | >90 | - |



UN No: 3264
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Toxic by inhalation.
 Causes burns.
 Risk of serious damage to eyes.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 * – limited evidence

PROPERTIES



Liquid. Mixes with water. Corrosive. Acid. Does not burn.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Flood body with water. Remove contaminated clothing. Wash with water.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Airway problems - 100% O₂. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.

Fire Fighting:

Keep surrounding area cool. Water spray/fog.

Spills and Disposal:

Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.BUTYL 2.NEOPRENE 3.HYPALON

Respirator:

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x — Must not be stored together