

## Henkel Loctite Heavy Duty Anti-Seize Lubricant

INGREDIENTS	CAS NO	%	8HR OEL
calcium fluoride	7789-75-5	10-30	2.5 mg/m3
graphite	7782-42-5	10-30	3 mg/m3
calcium stearate	1592-23-0	<10	10 mg/m3
calcium dodecylbenzenesulfonate	26264-06-2	<5	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### HEALTH HAZARD INFORMATION

### PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	PVC chemical resistant type.
<b>Respirator:</b>	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Keep out of reach of children.
<b>Fire/Explosion Hazard:</b>	Toxic smoke/fumes in a fire.
<b>Environment:</b>	Harmful to aquatic organisms.

### PROPERTIES



Liquid.  
 Does not mix with water.  
 Sinks in water. Combustible.

### EMERGENCY



### FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together