

VWR Calcium Standard Solution (1000ppm) for ICP, DCP,

INGREDIENTS	CAS NO	%	8HR OEL
nitric acid	7697-37-2	3-5	5.2 mg/m3
water	7732-18-5	>60	-



UN No: 3264 Hazchem Code: 2X DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

HEALTH HAZARD INFORMATION









Toxic by inhalation. Causes burns.

Risk of serious damage to eyes.

PRECAUTIONS FOR USE











Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	1.BUTYL 2.NEOPRENE 3.HYPALON
Respirator:	Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES





Liquid. Mixes with water. Corrosive. Acid.Does not burn.

EMERGENCY











FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
	Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose
Spills and Disposal:	of this material and its container at hazardous or special waste collection point. This material and its
z lopodan	operation and the material and the

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







material, use water.



container must be disposed of in a safe way. To clean the floor and all objects contaminated by this

Flammable Explosive Radioactive Oxidizing х х х

x — Must not be stored together