

ExxonMobil Mobiltac 375 NC

INGREDIENTS	CAS NO	%	8HR OEL
bitumen (petroleum)	8052-42-4	60-70	5 mg/m3
distillates, petroleum, middle, chemically-neutralised	64742-30-9.	10-20	5 mg/m3
isoparaffins petroleum hydrotreated HFP	64742-47-8.	10-20	790 mg/m3
2-ethylhexanoic acid, zinc salt	136-53-8	1-5	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **None**
 Subsidiary Risk: **None**
 Packing Group: **None**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type. Leather Gloves.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
 Does not mix with water.
 Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together