

HEMPLAIN ENAMEL 52140

INGREDIENTS	CAS NO	%	8HR OEL
solvent naphtha petroleum, medium aliphatic.	64742-88-7	35-50	5 mg/m3
petroleum distillates HFP	64742-48-9.	0.25-2.5	5 mg/m3
xylene	1330-20-7	1-5	350 mg/m3
C.I. Pigment Red 104 - Molybdate Orange	12656-85-8	5-25	10 mg/m3



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful if swallowed.
 May cause SENSITISATION by skin contact.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Danger of cumulative effects.
 Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
 May cause harm to the unborn child.
 Possible risk of impaired fertility.

* – limited evidence

PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Ipecac emesis. Chrome ulcers respond to CaNa2EDTA. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Diazepam is anti-convulsant of choice. BAL may be an effective antidote.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together