









ExxonMobil Mobilmet S-122

INGREDIENTS	CAS NO	%	8HR OEL
UN No: Not Applicable Hazchem Code: Not Applicable DG Class: None Subsidiary Risk: None Packing Group: None Poisons Schedule: Not Applicable		NFPA Rating: ▶ 0: Minimum ▶ 1: Low ▶ 2: Moderate ▶ 3: High ▶ 4: Extreme	
HEALTH HAZARD INFORMATION	PROPERTIES		
PRECAUTIONS FOR USE	   		
Appropriate engineering controls: General Exhaust Ventilation adequate.	  Liquid. Mixes with water. Combustible.		
Glasses: Consider chemical goggles.	EMERGENCY 		
Gloves: PVC chemical resistant type.	FIRST AID		
Storage and Transportation: Store in cool, dry, protected area.	Swallowed: Rinse mouth with water.		
Fire/Explosion Hazard: Vapours/gas heavier than air. Toxic smoke/fumes in a fire.	Eye: Wash with running water.		
	Skin: Remove contaminated clothing. Wash with soap & water.		
	Inhaled: Fresh air. Rest, keep warm.		
	Advice To Doctor: Treat symptomatically.		
	Fire Fighting: Water spray/ fog.		
	Spills and Disposal: Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.		
	SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS		

x — Must not be stored together