

## Magnaflux SKL-SP1

INGREDIENTS	CAS NO	%	8HR OEL
distillates, petroleum, light, hydrotreated	64742-47-8	>50	5 mg/m3
butane	106-97-8	<25	1900 mg/m3
diazo dye	Not Available	NotSpec.	-
phthalate ester	Not Available	NotSpec.	-



UN No: 1950  
 Hazchem Code: 2YE  
 DG Class: 2.1  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



**Acute Health Effects:** Irritating to skin.  
 Vapours may cause drowsiness and dizziness.

**Chronic Health Effects:** Repeated exposure may cause skin dryness and cracking.  
 \* – limited evidence

## PRECAUTIONS FOR USE



**Gloves:** When handling larger quantities:

**Respirator:** Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**Storage and Transportation:** Store in cool, dry, protected area.

**Fire/Explosion Hazard:** HIGHLY FLAMMABLE.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.  
 Risk of explosion if heated under confinement.

## PROPERTIES



Liquid.  
 Gas.  
 Does not mix with water.  
 Floats on water. Extremely flammable.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Do NOT give milk or oil. Do NOT give alcohol.
<b>Skin:</b>	Wash with soap & water. Apply cleansing cream.
<b>Advice To Doctor:</b>	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Keep containers cool. Water spray/ fog.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

			
Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together