

PPG Exterior Flat Acrylic Midtone Base

INGREDIENTS	CAS NO	%	8HR OEL
cristobalite	14464-46-1	1-5	0.1 mg/m3
titanium dioxide	1317-70-0	5-10	10 mg/m3
limestone	1317-65-3	1-5	10 mg/m3
Celite	68855-54-9	1-5	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Irritating to eyes.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

PROPERTIES



Liquid. Combustible.

EMERGENCY



FIRST AID

Swallowed: Rinse mouth with water.

Eye: Wash with running water.

Skin: Wash with soap

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Treat symptomatically.

Fire Fighting: Foam.

Spills and Disposal: Spilled liquid has low temperature and evaporates quickly.
 Eliminate ignition sources.
 Control vapour with water spray/ fog.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x

x

x

x

x — Must not be stored together