

DAP Weldwood Nonflammable Contact Adhesive

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	1-5	191 mg/m3
urea	57-13-6	1-5	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Harmful by inhalation and if swallowed.

Chronic Health Effects: Possible risk of harm to the unborn child.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: PVC chemical resistant type.

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
 Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Give milk or water. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Fire Fighting: Water spray/ fog.

Spills and Disposal: Eliminate ignition sources.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x x x

x — Must not be stored together