

Magnaflux 14 HF

INGREDIENTS	CAS NO	%	8HR OEL
isoparaffins petroleum hydrotreated HFP	64742-47-8.	>70	790 mg/m3
hydrocarbon propellant	68476-85-7.	0-30	1800 mg/m3
C.I. Pigment Black 11	1317-61-9	0-0.9	-



UN No: 1950
 Hazchem Code: 2YE
 DG Class: 2.2
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PROPERTIES



Liquid.
 Gas.
 Does not mix with water.
 Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Skin:

Wash with soap & water. Apply cleansing cream.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.
 Water spray/ fog.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.

PRECAUTIONS FOR USE



Gloves:

When handling larger quantities:

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

Fire/Explosion Hazard:

Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 Risk of explosion if heated under confinement.

Environment:

Very toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together