

PPG Machine Colorant G

INGREDIENTS	CAS NO	%	8HR OEL
ethylene glycol	107-21-1	10-30	10 mg/m3
talc	14807-96-6	10-30	3 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Harmful by inhalation and if swallowed. Irritating to respiratory system.

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: 1.NATURALRUBBER 2.NEOPRENE

Respirator: Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard: Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor: Emesis - test for acidosis/hypocalcaemia. Consider ethanol therapy.

Fire Fighting: Foam.

Spills and Disposal: Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x x x

x — Must not be stored together