

Henkel 635 Retaining Compound Slip Fit

INGREDIENTS	CAS NO	%	8HR OEL
acrylic acid	79-10-7	5-10	5.9 mg/m3
methacrylic acid	79-41-4	1-5	70 mg/m3
isopropyl benzene - cumene	98-82-8	1-5	125 mg/m3
2-hydroxypropyl methacrylate	923-26-2	30-60	-



UN No: 3082
 Hazchem Code: •3Z
 DG Class: 9
 Subsidiary Risk: None
 Packing Group: III
 Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful in contact with skin.
 Harmful if swallowed.
 Causes burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

May cause CANCER.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.SARANEX-23 2.TEFLON 3.VITON

Respirator:

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs. Handle and open container with care.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



2
 HAG18R19

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Flood body with water. Remove contaminated clothing. Wash with water

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Treat symptomatically.

Fire Fighting:

Keep containers cool. Water spray/ fog. Foam - alcohol type.

Spills and Disposal:

Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive

x

x

x — Must not be stored together