

QUICK DRYING ENAMEL No. 10182

INGREDIENTS	CAS NO	%	8HR OEL
lead chromate	7758-97-6	>10	0.05 mg/m3
aliphatic aromatic hydrocarbon	Not avail.	30-60	-
some colours may contain lead, as	Not Available	NotSpec.	-



UN No: 1263
 Hazchem Code: 3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: S6



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
 Irritating to eyes, respiratory system and skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Danger of cumulative effects.
 May cause CANCER.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
 May cause harm to the unborn child.
 Possible risk of impaired fertility.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid.
 Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Ipecac emesis. Chrome ulcers respond to CaNa2EDTA. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Diazepam is anti-convulsant of choice. BAL may be an effective antidote.
Fire Fighting:	Keep containers cool. Foam. Spilled liquid has low temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means.
Spills and Disposal:	Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x x x x x

x — Must not be stored together

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep out of reach of children.
 Keep container in a well ventilated place.
 Keep away from food, drink and animal feeding stuffs.
 Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.