

Fosroc Nitoseal 220 Accelerator

INGREDIENTS	CAS NO	%	8HR OEL
XYLENE	1330-20-7	>=60	350 mg/m3
dibutyltin dilaurate	77-58-7	10-30	0.1 mg/m3



UN No: 1992
 Hazchem Code: •3W
 DG Class: 3
 Subsidiary Risk: 6.1
 Packing Group: III
 Poisons Schedule: S7



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Contact Doctor or Poisons Centre. Give glass of water.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Wash with soap & water. Apply cleansing cream.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Management is primarily supportive.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Flammable	Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x	x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful in contact with skin.
 Toxic if swallowed.
 Irritating to eyes.
 Irritating to skin.
 Vapours may cause drowsiness and dizziness.
 Possible risk of irreversible effects.

Chronic Health Effects:

Toxic: danger of serious damage to health by prolonged exposure if swallowed.
 May impair fertility.
 May cause harm to the unborn child.

* — limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.