

Belzona 1321 (Ceramic S-Metal) Base

INGREDIENTS	CAS NO	%	8HR OEL
silica amorphous	7631-86-9	1-5	10 mg/m3
bisphenol A/ diglycidyl ether resin, liquid	25085-99-8	10-30	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **S5**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes and skin.
 May cause SENSITISATION by skin contact.

PRECAUTIONS FOR USE



Appropriate engineering controls: General Exhaust Ventilation adequate.

Glasses: Safety Glasses.
 Consider chemical goggles.

Respirator: Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment: Harmful to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water. Combustible.
 May form explosive peroxides.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x x x

x — Must not be stored together