

## Hempel HEMPADUR 45079

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	5-<10	350 mg/m3
ethylbenzene	100-41-4	<3	434 mg/m3
talc	14807-96-6	NotSpec.	3 mg/m3
bisphenol A/ diglycidyl ether resin, liquid	25068-38-6	15-<29	-



UN No: 1263  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful if swallowed.  
 Irritating to eyes.  
 Irritating to skin.  
 May cause SENSITISATION by skin contact.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVA 3.VITON

## Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

## Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid.Flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together