

Micro Ultra Filler P15-3

INGREDIENTS	CAS NO	%	8HR OEL
styrene	100-42-5	10-30	213 mg/m3
antimony trioxide	1309-64-4	5-10	0.5 mg/m3
talc	14807-96-6	10-30	2.5 mg/m3
titanium dioxide	13463-67-7	5-10	10 mg/m3



UN No: 1866
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S6



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Irritating to eyes.
 Irritating to respiratory system.
 Irritating to skin.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 May cause CANCER by inhalation.
 Possible risk of harm to the unborn child.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid.Flammable.

EMERGENCY



FIRST AID

Swallowed:

If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Treat symptomatically. Chelation with BAL for serious exposure. Assess airway and circulation. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together