

## Hempel'S Paint Stripper 99540

INGREDIENTS	CAS NO	%	8HR OEL
formaldehyde solutions - non flammable	50-00-0	<0.1	1.2 mg/m3
methylal	109-87-5	25-50	3110 mg/m3
ISOPROPYL ALCOHOL	67-63-0	5-10	983 mg/m3
METHANOL	67-56-1	1-<3	262 mg/m3



UN No: 1263  
 Hazchem Code: \*3Y  
 DG Class: 3  
 Subsidiary Risk: None  
 Packing Group: III  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Harmful if swallowed.  
 Irritating to eyes.  
 Irritating to respiratory system.  
 Irritating to skin.  
 Vapours may cause drowsiness and dizziness.  
 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

## Chronic Health Effects:

May cause CANCER.  
 May cause heritable genetic damage.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 Possible risk of impaired fertility.  
 Possible risk of harm to the unborn child.

\* – limited evidence

## PROPERTIES



Liquid. Mixes with water. R11R19

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
<b>Eye:</b>	Wash with running water (15 mins). Medical attention.
<b>Skin:</b>	Flood body with water. Remove contaminated clothing. Wash with water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Lavage up to 15 mins post- ingestion. Decontaminate with milk/water containing ammonium acetate. Emesis. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Water spray/ fog. Foam - alcohol type.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE 2.SARANEX-23 3.PE/EVAL/PE

## Respirator:

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking. Handle and open container with care.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Not recommended for interior use on large surface areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.