

Hempel'S Curing Agent 98550

INGREDIENTS	CAS NO	%	8HR OEL
XYLENE	1330-20-7	5-10	350 mg/m3
ethylbenzene	100-41-4	1-2.2	434 mg/m3
m-xylenediamine	1477-55-0	10-20	-
p-tert-butylphenol	98-54-4	10-<20	-



UN No: 3469
 Hazchem Code: •3W
 DG Class: 3
 Subsidiary Risk: 8
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid. Corrosive. Alkaline. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care. Irrigate eyes with saline. Supportive care. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Vegetable oils retard GI absorption. Saline catharsis or activated charcoal. Consider methylene blue for poisoning.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x x x x x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful in contact with skin.
 Harmful if swallowed.
 Very toxic by inhalation.
 Causes burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by inhalation.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of impaired fertility.

* — limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.VITON 2.PE/EVAL/PE 3.PVA

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

Environment:

May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.