

## NITRILE RUBBER/RESIN PLIBOND 30

INGREDIENTS	CAS NO	%	8HR OEL
methyl ethyl ketone	78-93-3	67	445 mg/m3
phenol	108-95-2	1.4	4 mg/m3
calcium carbonate	471-34-1	2-6	10 mg/m3
nitrile rubber	Not Available	14-18	-



UN No: 1133  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: **S5**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes, respiratory system and skin.  
 Vapours may cause drowsiness and dizziness.  
 Possible risk of irreversible effects.

## Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.BUTYL 2.PE/EVAL/PE 3.TEFLON

## Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.  
 Keep out of reach of children.  
 Keep container in a well ventilated place.  
 Keep away from sources of ignition. No smoking.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.  
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

## PROPERTIES



Liquid. Highly flammable.

## EMERGENCY



## FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice.

**Eye:** Wash with running water (15 mins). Medical attention.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

**Advice To Doctor:** Treat symptomatically.

**Fire Fighting:** Keep containers cool. Foam.

**Spills and Disposal:**  
 Eliminate ignition sources.  
 Consider evacuation.  
 Prevent from entering drains.  
 Contain spillage by any means.  
 Control vapour with water spray/ fog.  
 Absorb with dry agent.  
 Stop leak if safe to do so.  
 This material and its container must be disposed of in a safe way.  
 To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together