

## **HEMPATHANE TOPCOAT 5521**

| INGREDIENTS                               | CAS NO      | %      | 8HR OEL   |
|---|-------------|--------|-----------|
| butyl acrylate                            | 141-32-2    | <0.3   | 5 mg/m3   |
| xylene                                    | 1330-20-7   | 10-<20 | 350 mg/m3 |
| ethylbenzene                              | 100-41-4    | 3-<4.4 | 434 mg/m3 |
| naphtha petroleum, light aromatic solvent | 64742-95-6. | 10-<20 | -         |



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### **HEALTH HAZARD INFORMATION**

















**Acute Health** 

Harmful by inhalation.

Harmful in contact with skin.

Irritating to eyes. Effects: Irritating to skin.

> HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:**  Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

### PRECAUTIONS FOR USE













**Appropriate** engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.VITON

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88

or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

## **PROPERTIES**









Liquid. Does not mix with water. Sinks in water. Flammable.

#### **EMERGENCY**









## **FIRST AID**

Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Wash with running water.

Eye:

Remove contaminated clothing. Wash with soap &

Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Fire Fighting:

Foam.

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with

Spills and Disposal: dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

# SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Toxic

Radioactive Oxidizing

x x x x - Must not be stored together