

Carboline Carboguard 890 Part A

INGREDIENTS	CAS NO	%	8HR OEL
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	2.5-10	274 mg/m3
XYLENE	1330-20-7	2.5-10	350 mg/m3
ethylbenzene	100-41-4	<2.5	434 mg/m3
Toluene (Reference Fuel)	108-88-3	<1	191 mg/m3



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.
 Irritating to respiratory system.
 Irritating to skin.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 May cause CANCER by inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.TEFLON 2.VITON/CHLOROBUTYL

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Treat symptomatically. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x

x

x

x

x — Must not be stored together