

PPG Machine colorant W

INGREDIENTS	CAS NO	%	8HR OEL
ethylene glycol	107-21-1	10-30	10 mg/m3
titanium dioxide	1317-70-0	40-70	10 mg/m3
silica amorphous	7631-86-9	1-5	10 mg/m3
C9 alkylphenol ethoxylate, branched	68412-54-4	1-5	-



UN No: 3082
 Hazchem Code: •3Z
 DG Class: 9
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful if swallowed.
 Irritating to skin.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Safety Glasses.
 Consider chemical goggles.

Gloves:

1.NATURALRUBBER 2.NEOPRENE

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid. Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Emesis - test for acidosis/hypocalcaemia. Consider ethanol therapy.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Eliminate ignition sources.
 Pollutant.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive



Oxidizing

x x x
 x — Must not be stored together