

International Paint Interlac 665 Violet Blue

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, heavy, hydrodesulfurised	64742-82-1.	25-<50	790 mg/m3
Stoddard Solvent	8052-41-3.	<1	790 mg/m3
xylene	1330-20-7	<2.5	350 mg/m3
methyl ethyl ketoxime	96-29-7	<1	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES









Does not mix with water. Sinks in water.Flammable.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled: give oxygen. Medical attention.

Evaluate for respiratory distress. Consider lavage **Advice To** with cuffed tube. NO adrenalin. Doctor:

Foam.

Fire Fighting: Eliminate ignition sources. Prevent from entering drains.

Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

Spills and Disposal:

Dispose of this material and its container at hazardous or special waste collection point.

This material and its container must be disposed of in a safe way.

To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive х х

Toxic

Radioactive Oxidizing

х х

- Must not be stored together