

Kop-Coat Z*SPAR Splash Zone A-788 - 2-Part Epoxy Compound - Part A

INGREDIENTS	CAS NO	%	8HR OEL
talc	14807-96-6	10-20	2.5 mg/m3
magnesium carbonate	546-93-0	10-20	10 mg/m3
bisphenol A/ diglycidyl ether resin, liquid	25068-38-6	40-50	-
graded sand	14808-60-7.	20-30	0.1 mg/m3



UN No: 3082 Hazchem Code: •3Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: \$5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION















Acute Health Effects: Irritating to eyes.

Irritating to respiratory system.

Irritating to skin.

May cause SENSITISATION by skin contact.

Chronic **Health Effects:** May cause CANCER.

Toxic: danger of serious damage to health by prolonged exposure through inhalation.

* - limited evidence

PRECAUTIONS FOR USE











Appropriate
engineering
controls

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88

or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES







Liquid. Does not mix with water. Sinks in water. Combustible.

EMERGENCY











FIRST AID

Give water (if conscious). URGENT MEDICAL Swallowed: ATTENTION. Wash with running water. Eye:

> Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breath shallow, give Inhaled: oxygen. Medical attention.

Advice To Treat symptomatically. Doctor:

Fire Fighting: Keep containers cool. Foam.

> Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a

safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Flammable Explosive Radioactive Oxidizing

Spills and

Disposal:

x x x x

- Must not be stored together