

Silaprene Adhesive H5038

| INGREDIENTS | CAS NO | % | 8HR OEL |
|--|---------------|------|---------|
| naphtha petroleum, light solvent-refined | 64741-84-0 | 50 | 5 mg/m3 |
| zinc compounds | Not Available | 15.4 | - |



UN No: 1133
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic Health Effects: May cause CANCER. May cause heritable genetic damage.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: PVC chemical resistant type.

Respirator: Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep in a cool place. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard: HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES



Liquid.
 Does not mix with water.
 Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting: Keep containers cool. Foam.

Spills and Disposal: Spilled liquid has low temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing
 x x x x

x — Must not be stored together