

# Henry PG832 - Unfibered Aluminum Roof Coating

INGREDIENTS	CAS NO	%	8HR OEL
Stoddard Solvent	8052-41-3.	30-60	790 mg/m3
xylene	1330-20-7	1-5	350 mg/m3
silica crystalline - quartz	14808-60-7	<1	0.1 mg/m3
aluminium	7429-90-5	10-30	10 mg/m3



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### **HEALTH HAZARD INFORMATION**







**Acute Health** Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:**  Repeated exposure may cause skin dryness and cracking.

\* - limited evidence

## PRECAUTIONS FOR USE













Glasses:	Consider chemical goggles.	
Gloves:	PVC chemical resistant type.	
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)	
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.	
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.	
Environment:	Harmful to aquatic organisms.  May cause long-term adverse effects in the aquatic environment. Use appropriate container to	

avoid environmental contamination.

# **PROPERTIES**







Does not mix with water. Floats on water.Flammable.









#### **FIRST AID**

	Give water (if conscious). Seek medical advice.
Swallowed:	Do NOT give milk or oil.
	Do NOT give alcohol.

Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Deferoxamine is preferred chelator. **Advice To** 

Evaluate for respiratory distress. Consider lavage Doctor:

with cuffed tube. NO adrenalin.

Foam.

Dry agent. Fire Fighting:

Do NOT fight fire with BCF extinguisher.

Do NOT fight fire with water.

Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Toxic Radioactive Oxidizing х х х х

- Must not be stored together