

Rust Proof compound L

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	8032-32-4	15-25	790 mg/m3
mineral oil	8020-83-5	40-50	5 mg/m3
waxes	Not Available	30-40	-



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic Health Effects: Repeated exposure may cause skin dryness and

* - limited evidence

PRECAUTIONS FOR USE





controls:











Appropriate engineering Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

> Gloves: PVC chemical resistant type.

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or Respirator:

national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire.

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment. Use appropriate container to **Environment:** avoid environmental contamination.

Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES







Does not mix with water. Floats on water Flammable.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice.

Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water (15 mins). Medical Eye:

attention.

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Emesis generally unnecessary. Debride for

Advice To subcutaneous injection.

Evaluate for respiratory distress. Consider lavage Doctor:

with cuffed tube. NO adrenalin.

Fire Fighting: Foam.

> Eliminate ignition sources. Spills and Prevent from entering drains. Disposal:

Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS











Explosive

Toxic

X

Radioactive Oxidizing Х

- Must not be stored together