

Saudi Industrial Sipkyd Finish 430

INGREDIENTS	CAS NO	%	8HR OEL
mineral spirit	64475-85-0	30-40	-
alkyd resin - unregulated	63148-69-6	30-45	-



UN No: 1993 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Irritating to eyes and skin.

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES







Does not mix with water. Sinks in water.Flammable.

Remove contaminated clothing. Wash with soap &

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice.

Swallowed: Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Treat symptomatically.

Advice To Evaluate for respiratory distress. Consider lavage Doctor:

with cuffed tube. NO adrenalin.

Fire Fighting: Foam.

Skin:

Eliminate ignition sources. Spills and Disposal:

Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive х х

Toxic

х х

- Must not be stored together