

## MX2000

INGREDIENTS	CAS NO	%	8HR OEL
methyldiethanolamine	105-59-9	71-98	-
piperazine	110-85-0	<18	-
water	7732-18-5	<14	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Causes burns.  
 Risk of serious damage to eyes.  
 May cause SENSITISATION by inhalation.  
 May cause SENSITISATION by skin contact.

## Chronic Health Effects:

Possible risk of impaired fertility.  
 Possible risk of harm to the unborn child.  
 \* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider full face-shield.

## Gloves:

1.NEOPRENE 2.VITON 3.PVA

## Respirator:

Type AK Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters.

## Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid. Mixes with water. Combustible.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

## Eye:

Wash with running water (15 mins). Medical attention.

## Skin:

Flood body with water. Remove contaminated clothing. Wash with water

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Advice To Doctor:

Treat symptomatically. Assist ventilation Hypotension - Trendelenburg Position. Methylene blue for severe poisoning.

## Fire Fighting:

Water spray/ fog.

## Spills and Disposal:

Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

x

x

x — Must not be stored together