

# **Hach Formazin Turbidity Standard 4000 NTU**

INGREDIENTS	CAS NO	%	8HR OEL
formaldehyde	50-00-0	<0.1	1.2 mg/m3
hexamine	100-97-0	1-10	-
water	7732-18-5	>90	-
formazin polymer	Not Available	<1	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### **HEALTH HAZARD INFORMATION**





**Acute Health** Effects: May cause SENSITISATION by inhalation and skin

contact.

## PRECAUTIONS FOR USE













Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL 2.NEOPRENE 3.VITON
Respirator:	Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

### **PROPERTIES**





Liquid.

Mixes with water. Does not burn.







#### **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







x x x - Must not be stored together