

TRETOLITE*DM22874

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-30	350 mg/m3
kerosene	8008-20-6	30-60	-
(C10-16)alkylbenzenesulfonic acid	68584-22-5	1-5	-



UN No: 1993
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and in contact with skin.
 Irritating to skin.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

PROPERTIES



Does not mix with water.
 Floats on water.Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.VITON
Respirator:	Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms.Use appropriate container to avoid environmental contamination.