

M-I Pipe-Lax ENV

INGREDIENTS	CAS NO	%	8HR OEL
n-butanol	71-36-3	<5	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

HARMFUL-May cause lung damage if swallowed.

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

1.HYPALON 2.NEOPRENE 3.NITRILE

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid. Mixes with water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Rinse mouth with water.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm.

Fire Fighting: Water spray/ fog.

Spills and Disposal:

Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

x

x

x — Must not be stored together