

# PPG CA 8000/B4849 Desothane HS Gloss Green Base Component

INGREDIENTS	CAS NO	%	8HR OEL
amyl methyl ketone	110-43-0	10-30	233 mg/m3
xylene	1330-20-7	<5	350 mg/m3
methyl propyl ketone	107-87-9	<5	705 mg/m3
titanium dioxide	13463-67-7	<10	10 mg/m3



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### **HEALTH HAZARD INFORMATION**











Harmful by inhalation. Harmful if swallowed.

HARMFUL-May cause lung damage if swallowed.

Chronic **Health Effects:**  May cause CANCER by inhalation.

\* - limited evidence

## PRECAUTIONS FOR USE





**Appropriate** 









engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at

hazardous or special waste collection point.

### **PROPERTIES**





Liquid.Flammable.







### **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Consider sodium sulfate as cathartic. monitor urine/serum for renal failure. For severe poisoning, administer CaNa2EDTA. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.

# Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







x x x x



Toxic Radioactive Oxidizing

- Must not be stored together