

## Rocol Tufgear Spray

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	64742-88-7.	1-10	790 mg/m3
hydrocarbon propellant	68476-85-7.	50-70	1800 mg/m3
ACETONE	67-64-1	1-10	1185 mg/m3
alkanes, C7-8-iso-	70024-92-9	10-30	-



UN No: 1950  
 Hazchem Code: **Not Applicable**  
 DG Class: **2.1**  
 Subsidiary Risk: **None**  
 Packing Group: **None**  
 Poisons Schedule: **Not Applicable**



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### HEALTH HAZARD INFORMATION



#### Acute Health Effects:

Vapours may cause drowsiness and dizziness.

### PRECAUTIONS FOR USE



<b>Gloves:</b>	1.BUTYL 2.BUTYL/NEOPRENE 3.PVA
<b>Respirator:</b>	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from heat. Keep away from sources of ignition. No smoking.
<b>Fire/Explosion Hazard:</b>	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

### PROPERTIES



Liquid. Gas. Does not mix with water. Floats on water. Extremely flammable.

### EMERGENCY



### FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
<b>Skin:</b>	Wash with soap & water. Apply cleansing cream.
<b>Fire Fighting:</b>	Keep containers cool. Foam.
<b>Spills and Disposal:</b>	Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together