

Castrol Flick Easing Oil

INGREDIENTS	CAS NO	%	8HR OEL
1,1,1-trichloroethane	71-55-6	<25	555 mg/m3



UN No: 2831
 Hazchem Code: 2Z
 DG Class: 6.1
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Harmful by inhalation. Irritating to eyes.

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard: Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point.

Environment: Dangerous for the ozone layer. Use appropriate container to avoid environmental contamination.

PROPERTIES



Liquid. Does not mix with water. R04HAG18

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Assess airway and circulation. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting: Water spray/ fog.

Spills and Disposal: Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

x

x

x — Must not be stored together