

Reda RO IM C370

INGREDIENTS	CAS NO	%	8HR OEL
METHANOL	67-56-1	1-5	262 mg/m3
2-mercaptoethanol	60-24-2	5-10	-
benzyl C12-16-alkyldimethylammonium chloride	68424-85-1	5-10	-
fatty acids, tall oil, maleated	68139-89-9	1-5	-



UN No: 1760
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: None
 Packing Group: II
 Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful if swallowed.
 Causes severe burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.
 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure if swallowed.
 May cause harm to the unborn child.
 * – limited evidence

PROPERTIES



Liquid. Mixes with water. Corrosive. Acid. Alkaline. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins. Supportive care. Irrigate eyes with saline. Supportive care. Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.BUTYL 2.NEOPRENE 3.TEFLON

Respirator:

Type BKAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

X

X

X — Must not be stored together