

## Sanjel AI-8

INGREDIENTS	CAS NO	%	8HR OEL
propargyl alcohol	107-19-7	5-10	2.3 mg/m3
isopropanol	67-63-0	15-40	983 mg/m3
fatty acids	Not Available	NotSpec.	-
modified thiourea polymer	Not Available	NotSpec.	-



UN No: 1992  
 Hazchem Code: •3WE  
 DG Class: 3  
 Subsidiary Risk: 6.1  
 Packing Group: II  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## PROPERTIES



Liquid. Mixes with water. Highly flammable.

## EMERGENCY



## FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice.

**Eye:** Wash with running water (15 mins). Medical attention.

**Skin:** Wipe-off with clean/dry cloth. Remove contaminated clothing. Wash with water & soap. MEDICAL ATTENTION.

**Inhaled:** Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

**Fire Fighting:** Keep containers cool. Water spray/ fog. Foam - alcohol type.

**Spills and Disposal:** Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Harmful if swallowed.  
 Irritating to eyes.  
 Irritating to respiratory system.  
 Irritating to skin.  
 Vapours may cause drowsiness and dizziness.

## PRECAUTIONS FOR USE



**Appropriate engineering controls:** Local Exhaust Ventilation recommended.

**Glasses:** Consider chemical goggles.

**Gloves:** 1.NEOPRENE 2.NITRILE 3.PVC

**Respirator:** Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.