

ELEMENTAL MERCURY

INGREDIENTS	CAS NO	%	8HR OEL	
mercury (elemental)	7439-97-6	>98	0.025 mg/m3	



UN No: 2809 Hazchem Code: 2X DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: S7



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: Harmful if swallowed. Toxic by inhalation.

Chronic **Health Effects:** Danger of cumulative effects.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Type HG-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 Respirator:

or national equivalent)

Store in cool, dry, protected area.

Restrictions on Storage apply. Refer to Full Report.

Keep locked up.

Storage and Transportation:

Keep out of reach of children. Keep away from living quarters.

Keep away from food, drink and animal feeding

Fire/Explosion Hazard:

Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

In case of fire and/or explosion, DO NOT

BREATHE FUMES.

Environment:

Very toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment. This material and its container

must be disposed of as hazardous waste. Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES









Liquid. Does not mix with water.

Sinks in water.

Corrosive. Does not burn.

EMERGENCY









FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis or lavage for acute symptoms. Charcoal interrupts absorption.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Flammable Explosive Radioactive Oxidizing X x x

- Must not be stored together