

## Dow Corning 4 Electrical Insulating Compound

INGREDIENTS	CAS NO	%	8HR OEL
SILICA AMPHOROUS	7631-86-9	5-<10	2 mg/m3
dimethylsiloxane, methyl silsesquioxane	68037-74-1	70-90	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **None**  
 Subsidiary Risk: **None**  
 Packing Group: **None**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	General Exhaust Ventilation adequate.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	PVC chemical resistant type.
<b>Respirator:</b>	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area.
<b>Fire/Explosion Hazard:</b>	Toxic smoke/fumes in a fire.

## PROPERTIES



Liquid. Does not mix with water. Sinks in water. Combustible.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Rinse mouth with water.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

**x** — Must not be stored together