

Carboline Carboguard 690 Part B

INGREDIENTS	CAS NO	%	8HR OEL
m-xylene	108-38-3	2.5-<10	350 mg/m3
o-xylene	95-47-6	2.5-<10	350 mg/m3
p-xylene	106-42-3	2.5-<10	350 mg/m3
ethylbenzene	100-41-4	2.5-<10	434 mg/m3



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful in contact with skin.
 Harmful if swallowed.
 Irritating to eyes.
 Irritating to skin.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.HYPALON 2.VITON/CHLOROBUTYL

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid.Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Blow nose. Rinse mouth with water.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.

Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together