

2-METHYL-2-PROPANETHIOL

INGREDIENTS	CAS NO	%	8HR OEL
tert-butyl mercaptan	75-66-1	>98	-



UN No: 2347*
 Hazchem Code: •3WE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Respirator:	Type BAX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.

Does not mix with water.

Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Spilled liquid has low temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together