

Baker Tretolite DMO22121

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	10-30	350 mg/m3
methanol	67-56-1	10-30	262 mg/m3
isopropyl benzene - cumene	98-82-8	<1	125 mg/m3
naphthalene	91-20-3	<1	52 mg/m3



UN No: 1993
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **S6**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Toxic by inhalation, in contact with skin and if swallowed.
 Irritating to skin.
 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Does not mix with water.
 Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:

Give milk or water. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Wipe-off with clean/dry cloth. Remove contaminated clothing. Wash with water & soap.
MEDICAL ATTENTION.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
 Decontaminate with ipecac or lavage. Ethanol therapy.

Fire Fighting:

Keep containers cool.
 Foam.

Spills and Disposal:

Eliminate ignition sources.
 Consider evacuation.
 Prevent from entering drains.
 Contain spillage by any means.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.NITRILE

Respirator:

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.

Environment:

Toxic to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Flammable	Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x	x

x — Must not be stored together